

# Diffusers - Fixed flow rate




## Pokinor 3000



The fixed flow rate and selectable flow pattern diffusers (straight stream, attack spray, wide angle spray) are made of anodised primary aluminium alloy. The wide angle spray is obtained thanks to polyurethane teeth.

**Maximum working pressure:** PN16  
**Material:** aluminium alloy  
**Surface treatment:** hard anodisation and polyester coating  
**Stream types:** straight jet, flashover and wide angle spray  
**Head:** polyurethane teeth




Inlet	Flow rate (lpm)	Working pressure (bar)	Dimensions (mm)	Weight (kg)	Ref.
2.5" BSP male	3000	7	Ø214 x 162	3,45	<b>37333</b>

## Pokador 2000 - 3000



The fixed flow rate and selectable flow pattern diffusers (straight stream, attack spray, wide angle spray) are made of anodised primary aluminium alloy. The wide angle spray is obtained thanks to spinning teeth. They are designed to be used with POK monitor nozzles to obtain a quality spray and performance for an efficient firefighter.

**Maximum working pressure:** PN16  
**Material:** aluminium alloy  
**Surface treatment:** hard anodisation and polyester coating  
**Stream types:** straight jet, flashover and wide angle spray  
**Head:** spinning teeth




Inlet	Flow rate (lpm)	Working pressure (bar)	Dimensions (mm)	Weight (kg)	Ref.
2.5" BSP male	2000	7	Ø208 x 206	4,24	<b>18653</b>
2.5" BSP male	3000	7	Ø208 x 206	4,24	<b>18604</b>

## Pokatak 3000



The fixed flow rate and selectable flow pattern diffusers (straight stream, attack spray, wide angle spray) are made of anodised primary aluminium alloy. They are designed to be used with POK monitor nozzles to obtain a quality spray and performance for an efficient firefighter.

**Maximum working pressure:** PN16  
**Material:** aluminium alloy  
**Surface treatment:** hard anodisation  
**Stream types:** straight jet, flashover and wide angle spray  
**Head:** cut teeth




Inlet	Flow rate (lpm)	Working pressure (bar)	Dimensions (mm)	Weight (kg)	Ref.
2.5" BSP male	3000	7	Ø162 x 212	3,56	<b>32741</b>

## Pokabronze 2000 - 6000



The diffuser Pokabronze is made of bronze and stainless steel. With a flow rate of 2,000 or 6,000 lpm, and selectable flow pattern from straight spray to wide spray angle. It is designed to be used with POK bronze monitor, and used in marine environment.

**Maximum working pressure:** PN16  
**Material:** bronze and stainless steel  
**Stream types:** straight jet, flashover and wide angle spray  
**Head:** smooth (2000 lpm), cut teeth (6000 lpm)



Inlet	Flow rate (lpm)	Working pressure (bar)	Dimensions (mm)	Weight (kg)	Ref.
2.5" NST-NH female	2000	7	Ø221 x 137	4,31	<b>20102</b>
3" BSP female	6000	7	Ø263 x 358	15,73	<b>34477</b>