



T-FOAM 3



TECHNICAL DATA

1. DESCRIPTION

- **T-FOAM 3** is a training foam concentrate usable for firemen training on fires and fire fighting equipment testing.
- **T-FOAM 3** can be used at 3% on hydrocarbon fires.
- **T-FOAM 3** is a fluid newtonian liquid. It can be used with all existing dosing systems on the market.

2. PHYSICAL DATA

Aspect / Colour	Yellow liquid
Specific gravity at 20°C	1.01 +/- 0.01 Kg/dm3
pH at 20°C	6.0 - 8.0
Viscosity Brookfield at 20°C (30 rpm)	5
Freezing Point	-6°C
Sediments	< 0.1%
Surface tension at 1%	26-30 mN/m
Low expansion at 3%	10
Drainage time 25% / 50%	5 min. / 8 min.
Medium expansion at 3%	60

3. ENVIRONMENTAL DATA

- **T-FOAM 3** is a foam concentrate FLUORO-FREE FOAM. It does not contain any compound PBT : Persistent-Bioaccumulable – Toxic
- **T-FOAM 3** Is completely biodegradable

4. WARRANTY AND PRESENTATION

- **T-FOAM 3** is warranted for 10 years when kept in its original package.
- Storage temperatures are from -30°C to +60°C
T-FOAM 3 has an expected life span of 20 years, if kept at temperatures from 0°C to +40°C and away from sunlight.
- **T-FOAM 3** is not affected by cycles of freeze/thaw. It can be used after being frozen without any loss of efficiency.
- **T-FOAM 3** is drummed in jerricans of 20L/25/, in drums of 200 liters and in IBCs of 1000 liters. Drums are made of PEHD. (Poly Éthylène High Density)



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

TFOAM3-01 Révision Novembre 2022

Date d'impression: 15/12/2022

Page 1 de 1

www.3fff.co.uk